

# 2N® INDOOR TOUCH 2.0

ANSWERING UNIT FOR INTEGRATION WITH HOME AUTOMATION

The 2N® Indoor Touch 2.0 answering unit guarantees reliable video door communication. The Android OS, more powerful hardware and simple user interface make it easy to integrate the 2N® Indoor Touch 2.0 with third-party applications. For example, home automation systems can be comfortably operated on the 7" touch screen made of tempered glass.



reddot design award  
winner

- **Durable 7" HD touch screen**
- **Integration with home automation systems**
- **Easy connection via WiFi**
- **A clear, easy to use home screen**
- **Attractive, award-winning design**

## VARIANTS



### BLACK

91378375



### WHITE

91378375WH



### WHITE WiFi

91378376WH



### BLACK WiFi

91378376

## TECHNICAL PARAMETERS

### Power supply

Type	12V DC adapter or PoE 802.3af
Recommended power supply	12V/1A
Reverse polarity protection	Yes

### User interface

Controls	High-capacity touch screen
Display size	7" colour display
Display resolution	1024x600 px, 16:9
Backlighting	LED with eco mode
Status indicator	1x RGB LED (missed calls, eco mode, etc.)

### Operating system

Android 6.0

### Audio

Microphone	Integrated
Speaker	Integrated, 2W
Codecs	G.711, G.722, G.729

### Video

Codecs	H.264, MJPEG
--------	--------------

### Interface

LAN	10/100BaseT, RJ-45
Recommended cabling	Cat5e or better
WiFi (optional)	802.11b/g/n, integrated antenna
2x Relay	
2x GPIO (doorbell input, etc.)	
Memory card	MicroSD card (up to 16 GB)

### Mechanical parameters

Dimensions (W x H x D)	235 x 165 x 40 mm
Weight	850 g
Operating temperature	0°C to 60°C
Relative operating humidity	10% to 90% (non-condensing)
Storage temperature	-20°C to 70°C
Recommended altitude	0 to 2000m