Akuvox E12N

Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone E12N alerts you when the bell is rung and lets you see and speak with visitors from your smartphone, from anywhere.

At a Glance

- Real-time 2-way audio;
- Live camera viewing;
- Rated for outdoor use;
- Mobile App compatible;
- Complies with SIP standard for easy integration in every SIP capable PBXes;

Physical & Power

- Body Material: Plastic
- Camera: 2M pixels, automatic lighting
- Button: 1 call button with backlight
- Wiegand port: Support
- Light sensor: 1
- Relays out: 1
- Inputs: 2
- Micro SD card slot: 1
- Microphone: -36dB
- Speaker: 8Ω / 1.5W

- Ethernet port: RJ45, 10/100Mbps adaptive
- 12V DC connector (if not Power over Network)
- Water-proof & Dust-proof: IP65
- Installation: Wall-mounted
- Size: 146x70x23mm
- Working Humidity: 10~90%
- Working Temperature: -20°C ~ +60°C
- Storage Temperature: -40°C ~ +70°C



10/F, No.56 Guanri Road, Software Park II , Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694/8162 Fax: +86-592-2133 Email: sales@akuvox.com Web: www.akuvox.com



Datasheet

Akuvox E12N

Datasheet

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711µ, G.729
- Broadband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.7", CMOS
- Pixels: CIF, QCIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video resolution: up to 1920x1080p
- Max. image transfer rate: 1080p 25fps
- Viewing angle: 123°(H) / 69°(V)
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- Compatible to 3rd-Party-Video components, e.g. NVRs

Door Entry Feature

- Relay controlled individually by DTMF tones
- Camera permanently operational
- Auto-night mode with LED illumination
- White balance: auto
- Minimum illumination: 0.1LUX

Networking & Protocol

 Protocols support: IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)

Application Scenario

- Office door phone with on-site or hosted IP-PBX
- Remote site entry over Internet
- Apartment/flat intercom with door access control



10/F, No.56 Guanri Road, Software Park II -, Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694/8162 Fax: +86-592-2133 Email: sales@akuvox.com Web: www.akuvox.com Akuvox_20210917_V1.0