

The CyberData InformaCast Enabled Indoor Intercom with Keypad can receive InformaCast notification messages, deliver two-way communication and provide secure access control for your VoIP phone system. This device is perfect for settings such as commercial or residential facilities, schools, universities and retail establishments.

## InformaCast Features

- Capable of receiving Singlewire InformaCast notification messages
- Compatible with Singlewire InformaCast v12.1, including support for downloading SIP credentials from InformaCast
- Supports Singlewire InformaCast High Quality Audio

## Standard Features

- Compatible with Cisco Call Manager
- TLS 1.2 enhanced security for IP Endpoints in a local or cloud-based environment
- Dry contact relay configurable in all modes for secure access or auxiliary control
- Security mode allows for up to 500 user codes with configurable times and blacklisting plus extension dialing
- 12-key keypad with backlight
- Programmable speed dial
- Full-duplex voice operation
- Supports SRST (Survivable Remote Site Telephony) in a Cisco environment
- Enhanced acoustic echo canceling
- Network web management and firmware download
- Network adjustable volume
- Concurrent SIP and multicast paging
- Door closure and tamper alert signal
- Downloadable alert, ringtone and callout messages





## Specifications

Ethernet I/F	10/100 Mbps
Protocol	SIP RFC 3261 Compatible
Notification Software	Singlewire InformaCast v4.0 and above
Power Input	PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply (not included)
Speaker Output	2 Watts Peak Power
On-Board Relay	1A @ 30 VDC
Payload Types	G.711 a-law, G.711 μ-law, G.722, and G.729
Network Security	TLS/SSL 1.2
Operating Range	Temperature: -40° C to 55° C (-40° F to 131° F) Humidity: 5-95%, non-condensing
Storage Temperature	Temperature: -40° C to 70° C (-40° F to 158° F)
Storage Altitude	Up to 15,000 ft. (4573 m)
Dimensions*	6.50 inches [165.0 mm] Length 1.90 inches [48.2 mm] Width 4.53 inches [115.0 mm] Height
Weight	1.2 lbs. [0.54 kg]
Boxed Weight	2.0 lbs. [0.90 kg]
Compliance	CE; EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive – EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant
Warranty	2 Years Limited
Part Number	011307

\*Dimensions are measured from the perspective of the product being upright with the front of the product facing you.

# InformaCast® Enabled Indoor Intercom with Keypad



## Related Products:



**011375 Network Dual Door Strike Relay**



**011269 Door Strike Intermediate Relay Module**



**011288 Auxiliary RGB (Multi-Color) Strobe Kit**