

Epygi's QX products are compact, fully rack-mountable and housed in a metal enclosure. They are made to mix and match for a fully customizable system to fit every consumer's specific needs. With the purchase of a rack-mounting kit, the units also come with two DC power cables for power redundancy. With built-in auto-configuration, firewall and secure VPN support, Epygi's QX IP PBXs and Gateways are SIP-compliant and designed for a more user-friendly experience. Our PBXs come with a wide range of useful telephony features specific to your company's unique needs with ease of installation, maintenance and use. The Gateways can be utilized to include additional FXO, FXS, T1 or E1 ports to any of Epygi's or other manufacturer's IP PBXs. Integrating an Epygi QX Gateway with any QX IP PBX allows for the Gateway to be managed through the IP PBX's GUI. Epygi is also cross-certified with a broad selection of IP phones and SIP trunk providers, in order to provide you with a completely integrated communications package.

QX IP PBXs



Capabilities		
IP phones	12	
Additional IP phones with keys	20	
Total phones	32	
Concurrent calls	6	
Additional concurrent calls with keys	4	
Ethernet LAN ports	2	
Ethernet WAN ports	1	
Audio In port	1	
Audio Out port	1	
SD slot	1	

Interconnection with QX Gateways	
GATEWAYS	Recommended Number (max)
QXFXO4	2
QXISDN4	1
QXE1T1	1
QXFXS24	1



Capabilities	
Analog phones	2
IP phones	16
Additional IP phones with keys	32
Total phones	50
Concurrent calls	16
FXO PSTN ports	2
Ethernet LAN ports	1
Ethernet WAN ports	1
Audio In port	1
Audio Out port	1
SD slot	1

Recommended Number (max)
4
2
1
2

Capabilities		Inte
IP phones	24	
Additional IP phones with keys	40	GA
Total phones	64	QX
Concurrent calls	20	QX
Ethernet LAN ports	2	QX
Ethernet WAN ports	1	
Audio In port	1	QX
Audio Out port	1	
SD slot	1	

Interconnection with QX Gateways	
GATEWAYS	Recommended Number (max)
QXFXO4	5
QXISDN4	2
QXE1T1	1
QXFXS24	3

	_	
Capabilities		Interco
Analog phones	2	
IP phones	24	GATE
Additional IP phones with keys	176	QXF)
Total phones	202	QXIS
Concurrent calls	64	
FXO PSTN ports	4	QXE1
Ethernet LAN ports	1	QXF)
Ethernet WAN ports	1	
Audio In port	1	
Audio Out port	1	
SD slot	1	

Interconnection with QX Gateways	
GATEWAYS	Recommended Number (max)
QXFXO4	16
QXISDN4	8
QXE1T1	2 (E1 mode), 3 (T1 mode)
QXFXS24	8

Capabilities
IP phones
Additional IP phones with keys
Total phones
Concurrent calls

1

1

1

1

QX100

Ethernet LAN ports Ethernet WAN ports

Audio In port

Audio Out port

SD slot

Interconnection with QX Gateways	
GATEWAYS	Recommended Number (max)
QXFXO4	10
QXISDN4	5
QXE1T1	1 (E1 mode), 2 (T1 mode)
QXFXS24	5



Capabilities	
IP phones	100
Additional IP phones with keys	400
Total phones	500
Concurrent calls	80
Ethernet LAN ports	2
Ethernet WAN ports	1
Audio In port	1
Audio Out port	1
SD slot	1

Interconnection with QX Gateways	
GATEWAYS	Recommended Number (max)
QXFXO4	20
QXISDN4	10
QXE1T1	3 (E1 mode), 4 (T1 mode)
QXFXS24	16

QX3000

Capabilities		Interconnection	with QX Gateways		
IP phones	200	GATEWAYS	Recommended		
Additional IP phones with keys	2,800		Number (max)		
Total IP phones	3,000	QXFXO4	32		
Concurrent calls	500	QXISDN4	32		
Ethernet LAN ports	1	QXE1T1	16 (E1 mode), 20 (T1 mode)		
Ethernet backup	1	QXFXS24	100		



c cpygi

Capabilities	
IP phones	500
Additional IP phones with keys	4,500
Total IP phones	5,000
Concurrent calls	700
Ethernet LAN ports	1
Ethernet backup	1

Interconnection with QX Gateways			
GATEWAYS	Recommended Number (max)		
QXFXO4	32		
QXISDN4	32		
QXE1T1	20 (E1 mode), 24 (T1 mode)		
QXFXS24	100		

Licensable Features for QX IP PBXs

Epygi's QX line comes equipped with many free features and the availability to select from an extensive array of additional features for purchase. Licensable features range from call center solutions to video conferencing, to allow for a custom UC solution for your business without incurring unnecessary costs.

Features	QX20	Q×50	QX60	Q X100	<mark>Q</mark> X200	Q ×500	Q×3000	<mark>Q×</mark> 5000
IP Phone Expansion Key - This phone expansion key enables additional local IP phone extensions on the IP PBXs.	4, 8, 16 ext. Max 32 IP phones	4, 8, 16, 32 ext. Max 48 IP phones	4, 8, 16, 32 ext. Max 64 IP phones	4, 8, 16, 32, 64 ext. Max 128 IP phones	4, 8, 16, 32, 64, 128 ext. Max 200 IP phones	4, 8, 16, 32, 64, 128, 256 ext. Max 500 IP phones	4, 8, 16, 32, 64, 128, 256, 512, 1024 ext. Max 3,000 IP phones	4, 8, 16, 32, 64, 128, 256, 512, 1024 ext. Max 5,000 IP phones
Concurrent Call Expansion Key - Allows additional concurrent calls.	2, 4 Expansion Key Max 10 concr. calls	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Audio Conference Key - An integrated conferencing feature that allows your company to stay connected and current around the globe.	4, 8, 16 users Max 16 users	4, 8, 16 users Max 16 users	4, 8, 16 users Max 16 users	4, 8, 16, 32 users Max 32 users	4, 8, 16, 32 users Max 32 users	4, 8, 16, 32 users Max 48 users	4, 8, 16, 32 users Max 288 users Max 95 users in 1 conf. bridge	4, 8, 16, 32 users Max 288 users Max 95 users in 1 conf. bridge
Video Conference Server - As an add-on feature to the Audio Conference Key, companies can view both local and remote users' video on the QX.	8 users Max 8 video users	8 users Max 8 video users	8 users Max 8 video users	8 users Max 16 video users	8 users Max 16 video users	8 users Max 24 video users	8 users Max 104 video users Max 48 users in 1 conf. bridge	8 users Max 104 video users Max 48 users in 1 conf. bridge
Automatic Call Distribution (ACD) - Used by call centers to handle basic inbound call queuing and distributing the calls to the agents.	N/A	Small All users can be configured as agents	Medium All users can be configured as agents	Enterprise All users can be configured as agents	Enterprise All users can be configured as agents			
Epygi ACD Console (EAC) - This per-seat web based application gives agents and supervisors full control of their call center.	N/A	1, 5,10 users Max 15 users*	1, 5,10, 20 users Max 20 users*	1, 5,10, 20 users Max 30 users*	1, 5,10, 20 users Max 30 users*	1, 5,10, 20 users Max 50 users*	1, 5,10, 20 users Max 300 users*	1, 5,10, 20 users Max 300 users*
Barge-In - Silent Monitoring, Agent Whisper and Supervisor features can be an add-on to the Automatic Call Distribution or as a stand- alone feature.	N/A	Medium Activates feature for all users	Medium Activates feature for all users	Medium Activates feature for all users	Medium Activates feature for all users	Enterprise Activates feature for all users	Enterprise Activates feature for all users	Enterprise Activates feature for all users
Call Recording - Record PBX, SIP or PSTN calls on the QX. Store the recordings either locally on the QX by using internal memory or on an external server.	2, 4, 8 ports Max 10 ports	<mark>2, 4, 8 ports</mark> Max 12 ports	<mark>2, 4, 8 ports</mark> Max 24 ports	2, 4, 8 ports Max 32 ports	2, 4, 8, 16 ports Max 32 ports	2, 4, 8, 16, 32 ports Max 48 ports	2, 4, 8, 16, 32 ports Max 240 ports	2, 4, 8, 16, 32 ports Max 320 ports

* The number of active EAC sessions may vary depending on the system load by other IP PBX processes, such as the Call Recording.



Licensable Features for QX IP PBXs

Features	<mark>Q</mark> X20	Q X50	<mark>QX</mark> 60	Q X100	005XQ	Q X500	Q×3000	<mark>Q</mark> ×5000
Calling Cost Control - Allows to limit and control the calling costs when making calls through payable routing rules.	Small Activates feature for all users	Small Activates feature for all users	Medium Activates feature for all users	Medium Activates feature for all users	Medium Activates feature for all users	Medium Activates feature for all users	Enterprise Activates feature for all users	Enterprise Activates feature for all users
Automatic Outbound Calling (AOC) - Automates outbound calls directly to clients.	N/A	<mark>1, 5</mark> Concurrent Calls Max 16 Calls	1, 5, 10 Concurrent Calls Max 20 Calls	1, 5, 10 Concurrent Calls Max 40 Calls	1, 5, 10 Concurrent Calls Max 64 Calls	1, 5, 10 Concurrent Calls Max 80 Calls	1, 5, 10 Concurrent Calls Max 500 Calls	1, 5, 10 Concurrent Calls Max 700 Calls
Third Party Call Control (3PCC) - The QX has a full featured Application Programming Interface (API). Apps can be designed to gain direct access to the QX IP PBX to enhance the feature offerings of this system.	Small 3PCC Activation License	Small 3PCC Activation License	Medium 3PCC Activation License	Medium 3PCC Activation License	Medium 3PCC Activation License	Medium 3PCC Activation License	Enterprise 3PCC Activation License	Enterprise 3PCC Activation License
System Redundancy Activation - 1+1 redundancy design where a second unit is running as an active standby unit.	N/A	Small Secondary unit must be purchased.	Medium Secondary unit must be purchased.	Medium Secondary unit must be purchased.	Medium Secondary unit must be purchased.	Medium Secondary unit must be purchased.	Enterprise Secondary unit must be purchased.	Enterprise Secondary unit must be purchased.
Epygi Hotel Console (EHC) - Allows efficient phone call handling, billing, and ad- vanced features like real-time room status updates, scheduled wake-up calls, do-not-disturb options, and easy minibar management.	N/A	EHC Small Activation Key	EHC Medium Activation Key	EHC Medium Activation Key	EHC Medium Activation Key	EHC Medium Activation Key	EHC Enterprise Activation Key	EHC Enterprise Activation Key
eQall Softphone - Compat- ible with MS Windows and mobile devices running on Android and iOS. It is a full desk phone replacement and is intended to be used with QX PBXs and ecQX. After activation it registers as an extension to the QX/ecQX system and operates like a normal PBX extension.	4, 8, 16, 32 users Max 32 ports	4, 8, 16, 32 users Max 48 ports	4, 8, 16, 32, 64 users Max 64 ports	4, 8, 16, 32, 64 users Max 128 ports	4, 8, 16, 32, 64 users Max 200 ports	4, 8, 16, 32, 64 users Max 500 ports	4, 8, 16, 32, 64 users Max 3000 ports	4, 8, 16, 32, 64 users Max 5000 ports
eQall Receptionist Console - Available for Windows. It allows watching the call status of up to 100 selected extensions on the QX.	Per 1 seat	Per 1 seat	Per 1 seat	Per 1 seat	Per 1 seat	Per 1 seat	Per 1 seat	Per 1 seat
eQall SMS/WhatsApp Messaging - Allows sending or receiving SMS/WhatsApp messages by eQall extensions globally.	2000, 4000, 8000 Messages	2000, 4000, 8000 Messages	2000, 4000, 8000 Messages	2000, 4000, 8000 Messages	2000, 4000, 8000 Messages	2000, 4000, 8000 Messages	2000, 4000, 8000 Messages	2000, 4000, 8000 Messages
Auto Dialer Activation - Automate outbound calls directly to clients.	N/A	1 port	1 port	1 port	1 port	1 port	1 port	1 port
Auto Dialer Expansion Key - Increases the number of concurrent outbound calls by one on the Auto Dialer Activation.	N/A	<mark>1 port</mark> Max 16 ports	<mark>1 port</mark> Max 20 ports	<mark>1 port</mark> Max 40 ports	<mark>1 port</mark> Max 64 ports	<mark>1 port</mark> Max 80 ports	<mark>1 port</mark> Max 100 ports	<mark>1 port</mark> Max 150 ports
CRM Integration - When activated, the per-seat license provides integration with Salesforce, Vtiger, Zoho CRM.	Per 1 seat	Per 1 seat	Per 1 seat	Per 1 seat	Per 1 seat	Per 1 seat	Per 1 seat	Per 1 seat
Voicemail Transcription - OpenAl-powered feature, converts voicemail messages into text and sends them to users via email notifications.	400, 800, 1600 Minutes	400, 800, 1600 Minutes	400, 800, 1600 Minutes	400, 800, 1600 Minutes	400, 800, 1600 Minutes	400, 800, 1600 Minutes	400, 800, 1600 Messages	400, 800, 1600 Minutes

@epygi[•] QX Gateways



Capabilities				
E1/T1 port	1			
Ethernet LAN ports	1			
Ethernet WAN ports 1				
Call Routing capable of modifying caller ID or time of day routing				
Firewall, VPN Router, Auto Attendant, Stacking Options, Failover				

QXFXS24



Capabilities				
FXS ports	24			
Ethernet LAN ports 1				
Ethernet WAN ports 1				
Call Routing capable of modifying caller ID or time of day routing				
Firewall, VPN Router, Stacking Options, Failover				

QX Gateway Converted to IP PBX



Capabilities					
IP phones	16				
Additional IP phones with keys	32				
Total phones	48				
Concurrent calls	16				
ISDN BRI ports 4					
Ethernet LAN ports 1					
Ethernet WAN ports 1					
Call Routing capable of modifying caller ID or time of day routing					
Firewall, VPN Router, Auto Attendant, Stacking Options, Failover					

Licensable Features for QX Gateways	QXE1T1	QXFXO4	QXFX524	QXISDN4
Gateway Hosted Survivability Ensure uninterrupted communication for your company, even during broadband link or Hosted PBX outages. This feature not only keeps your telephones functional but also allows users to provide access to remote phones in branch offices.	Available	Available	N/A	N/A
QXISDN4+ IP PBX Activation Once installed and activated, the Gateway will function as an IP PBX and cannot be changed back. All the applicable QX50 feature licenses can be purchased and activated, except for ACD, AOC and EAC licenses. The QXISDN4+ doesn't support Audio In, Audio Out and a SD card.	N/A	N/A	N/A	Available

QXFXO4



Capabilities				
FXO PSTN ports	4			
Ethernet LAN ports 1				
Ethernet WAN ports 1				
Call Routing capable of modifying caller ID or time of day routing				
Firewall, VPN Router, Auto Attendant, Stacking Options, Failover				

QXISDN4



Capabilities				
ISDN BRI ports	4			
Ethernet LAN ports 1				
Ethernet WAN ports 1				
Call Routing capable of modifying caller ID or time of day routing				
Firewall, VPN Router, Auto Attendant, Stacking Options, Failover				

Epygi Technologies, LLC 561 Maitland Ave Altamonte Springs, Florida 32701