

Cohesive DB3200A FXS VoIP Gateway

The Cohesive 32 ports analog FXS gateway provides a simple and affordable solution for legacy telephone, fax machines, and PBXs to interconnect with an IP network. This enables call centers and multi-branch enterprises to leverage powerful, versatile, and efficient VoIP solutions with significant cost advantages. By connecting the 32 ports FXS VoIP Gateway between a PBX, LAN, or WAN, the analog PSTN messages can be converted into a format suitable for transmission over standard IP networks.



The 32 Ports Analog VoIP Gateway DB3200A is specifically designed for voicemail and unified messaging applications and features a 10/100/1000M (optional) Base-T Ethernet connection to connect legacy PBXs to a LAN. The analog loop start functionality supports integration via in-band signaling (DTMF or FSK), serial protocols, as well as T.38 for fax transmissions over IP (FoIP).



DB3200A

Features

- Hotline extension setting
- Consol access via Telnet, SSH.
- Web-based remote administration
- Caller ID presentation and restriction
- Real-time call record send to CDR server
- Manageable based call routing TDP-IP/IP-TDM
- Restrict unwanted calls with list of denied numbers
- Make and receive IP calls from analog extensions
- Easy integration with existing telephony interfaces
- Completely non-blocking architecture and Scalable System
- Call budgeting based on allocated amount, minutes and call count
- Open-standard SIP support and register to multiple SIP proxy servers

Benefits of

- Primary/Backup SIP Servers
- Support SNMP/TR069/Auto-Provision
- Flexible routing and manipulation
- Data/voice/management VLAN and more
- Build-in firewall and access rules
- Easy to install, configure, and maintain
- Support IPv4 and IPv6 international network
- High performance VoIP connectivity for SMBs
- Cloud-based management and bandwidth optimization
- Support SIP, MGCP or other customizable protocols
- Voice optimization to ensure better user experiences
- Enhanced call routing ability with high voice quality

- Support 32 FXS Ports, Field Approved Globally
- Superior Voice Quality by Designated DSP Chipsets
- User-Friendliness and Web-based Administration

Technical Specifications:

Physical Interface

Phone Interface: 32 Ports FXS, RJ-11 available as well
Ethernet Interface: 2* RJ-45 10/100Mbps Base-T Ethernet,
Female RJ-45
1000M LAN/WAN available for some product models while
required

Session Capacity

32 SIP channels
32 FXS channels

Connectivity

Dial Mode: DTMF and Pulse
Pulse: 10 and 20PPS
Caller ID: DTMF/FSK
Max Cable Length: 5KM
Reversed Polarity
OpenVPN

VoIP Protocols

TLS / SRTP
OpenVPN
SIP V2.0 (RFC 3261, 3262, 3264)
IMS/3GPP
SDP
REFER (RFC 3515)
RTP/RTCP
STUN (RFC3489)
ARP/RARP (RFC 826/903)
SNTP (RFC 2030)
DHCP/PPPoE
TFTP/HTTP/HTTPS
DNS/DNSSRV (RFC 1706/RFC2782).
VLAN802. 1P/802.1Q.

Call & Routing

Port Groups
IP Trunks
Primary and Secondary SIP Account
32 Inbound/Outbound Routing Number
Manipulation
Digit maps
TDM to IP or IP to TDM
IP load balancing
IP fault tolerance

Voice Capability

G.711A/U law, G.723.1, G.729A/B,G.726,iLBC,AMR
Comfort Noise Generation(CNG)
Echo Cancellation(G.168)
DTMF mode: Signal/RFC2833/INBAND
Silence suppression with comfort noise
G.168 automatic echo cancellation
Call Progress Analysis (CPA), including Positive
Voice Detection, Positive

Answering

Machine Detection (PAMD), DTMF detection, and fax tone
detection
Manageable based call routing TDP-IP/IP-TDM.
Restrict unwanted calls with list of denied numbers.
Voice Activity Detection (VAD)
Adaptive (Dynamic) Jitter Buffer
Programmable Gain Control
Hook Flash

FoIP Protocol & Faxing

T.38 for transmission over a packet network
T.38/Pass-through, up to 14.4kbps

T.38 FoIP: transcode fax from T.30 fax protocol (supporting V.17) modulation schemes

Network Capability

Static IP, PPPoE, DHCP Client

IPv4, IPv6

Static/dynamic ARP

DIFFServ, ToS

NAT (Rout and Bridge)+

MAC Address Clone

Static routing+

Built-in Firewalls

QoS, Traffic Shaping

Voice/Data/Management Vlan

Maintenance & Upgrading

SNMP/TR069

Auto Provision

Action URL

Digit map

Web/Telnet. ACL

Configuration Backup/Restore

Bandwidth Optimization

Routing Rules based Prefixes

Firmware Upgrade via WEB

Syslog and CDR.

Access Rule list.

Network Capture

Outward Test(GR909).

Automatic Time Synchronization

IVR local Maintenance.

Cloud-based Management

Caller/Called Number Manipulation

Open-standard SIP support and register to multiple SIP proxy servers.

Application Capabilities

Call waiting, Blind Transfer, Attend Transfer

Call forward on Busy

Call forward on No Reply

Unconditional Call Forward

Hotline Call hold

DND

Call Pickup

3-way conference

Voicemail

Conferencing Resource

Call budgeting based on allocated amount, minutes and call count

Complete non-blocking architecture and Scalable System

Hotline extension setting

Support 3-Way and Multi-Way Conferencing

Environment & Power

Power Supply: 100-240V, 50-60Hz+

Power Consumption: Approximately 50W

Temperature(Operation): 0 °C ~ 45°C

(Storage): -20 ~85°C

Humidity: 10%-90% No condensation.

Operating temperature range: -10 °C ~55°C

Physical Dimension

L*W*H 440(mm)*202(mm)*44(mm)

Weight Approximately 5.95lbs(about 2.7kg)

Warranty/Certifications

1 year warranty

CE, FCC or Any other Certificates Customizable

Broadsoft, Elastix, Asterisk, Teams and other UC platform