



**WI-PS208H**  
**8-Port 48V 100Mbps PoE Switch**  
**Data sheet**

## Highlights

- 8 100Mbps PoE Ports
- Supports 250meters Long-Range PoE transmit
- Supports PoE IEEE 802.3af/at compliant PDs
- Internal power adapter supply 65W output power
- Support Port VLAN(Port isolation)
- LED indicators for LINK/ACT, Power, PoE Status, 100Mbps
- 4K entry MAC address table with auto-learning and auto-aging



## Typical Applications



## Description

### **what this product does**

WI-PS208H is a 8-port 10/100Mbps unmanaged switch that requires no configuration and provides 8 PoE ports. The switch provides an easy way to expand your wired network. All 8 ports support auto-MDI/MDIX, eliminating the need to worry about the type of cable to use. Featuring full duplex mode, the WI-PS208H can process data at a rate of up to 200Mbps making it an ideal choice for expanding your high performance wired network. Moreover, with innovative energy-efficient technology, the WI-PS208H can save up to 68% of power consumption, making it an eco-friendly solution for your home or office network.

### **High Performance**

WI-PS208H Fast Ethernet Switch provides 8 10/100Mbps Auto-Negotiation RJ45 ports. All ports support Auto MDI/MDIX function, eliminating the need for crossover cables or Uplink ports. Featuring non-blocking switching architecture, WI-PS208H forwards and filters packets at full wire-speed for maximum throughput. And IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode alleviate the traffic congestion and make WI-PS208H work reliably.

### **Easy to Use**

The auto features of this Ethernet switch make installation plug and play and hassle-free. No configuring is required. Auto MDI/MDIX eliminates the need for crossover cables. Auto-negotiation on each port senses the link speed of a network device (10, 100 Mbps) and intelligently adjusts for compatibility and optimal performance.

## Specifications

HARDWARE FEATURES	
<b>Interface</b>	8 10/100Mbps RJ45 Ports
<b>Network Media</b>	10/100BASE-TX: UTP category 5 or better (maximum 250m)
<b>Fan Quantity</b>	Fanless
<b>Power Consumption</b>	65W (max. with PoE device connected)
<b>Power Supply</b>	Internal Power Adapter(Output: DC52V 1.25A)
<b>PoE Ports (RJ45)</b>	Standard: 802.3 af/at compliant PoE Ports: Port1- Port8
<b>Backplane Bandwidth</b>	16Gbps
<b>Mac Address Table</b>	4K
<b>Packet Forwarding Rate</b>	1.2Mpps
<b>Buffer</b>	768Kbps
<b>Jumbo Frame</b>	10240Bytes

## HARDWARE FEATURES

<b>Dimensions</b>	
-------------------	--

## SOFTWARE FEATURES

<b>Transmission Method</b>	Store-And-Forward
<b>Advanced Functions</b>	Priority Function Mac Address Auto-Learning And Auto-Aging Store and forward IEEE 802.3x flow control for Full-duplex Mode Backpressure for Half-duplex Mode

## OTHERS

<b>Certification</b>	CE, FCC, RoHS
<b>Package Contents</b>	POE Switch Electric Line Guide Book/Warranty Card
<b>Environment</b>	Operating Temperature: -10°C~55°C