

SIP Paging Zone Controller with 4-Port Audio Out

Now Supports Up To 9 Stored Messages

The CyberData VoIP Zone Controller with Audio-Out enables access to existing paging speakers through a VoIP phone system. The interface is designed to use a standard paging amplifier with audio inputs and supports paging up to 15 zone groups from a VoIP phone.

Can receive pages directly from Polycom phones

New Features

- Now Supports Up To 9 Stored Messages
- Delayed paging
- Night Ringer
- Compatible with more IP/PBX servers

Features

- Page to Polycom phones
- SIP RFC 3261 compatible
- PoE 802.3af enabled (Power-over-ethernet)
- Dual-speed ethernet 10/100 Mbps
- 4 Paging zones
- 15 Paging zone groups
- Page all
- Web-based configuration
- Web-based firmware upgradeable
- Connector for external power supply
- Small footprint



Specifications

Protocol	SIP RFC 3261 Compatible
Ethernet I/F	10/100 Mbps
Power Input	PoE 802.3af or 48VDC
Operating Range	Temperature: -40° C to 55° C (-40° F to 131° F) Humidity: 5-95%, non-condensing
Storage Temperature	Temperature: -40° C to 70° C (-40° F to 158° F)
Storage Altitude	Up to 15,000 ft. (4573 m)
Payload Types	G711
Output Signal Amplitudes	2.0 VPP maximum
Output Level	+2dBm nominal
Total Harmonic Distortion	0.5% maximum
Dimensions	6.2 inches [157.48 mm] Length 4.5 inches [114.30 mm] Width 1.22 inches [30.98 mm] Height
Weight	1.6 lbs. (0.73 kg)
Boxed Weight	3.0 lbs. (0.82 kg)
Warranty	2 years limited
Part Number	011171

SIP Paging Zone Controller with 4-Port Audio Out

