





Cohesive E12 SIP Video Door Intercom

Compact, Stylish and Versatile, Perfect for Every Front Door

E12 is a single-button SIP video door phone for all types of front doors, be it houses, apartments, or condos. Despite a slim body, it boasts many cutting-edge features, such as mobile access and wireless communication.



Features

- H.265, IP65, Onvif, PoE, Wiegand
- Real-time 2-way talk
- Live camera viewing
- Cloud or local based storage
- Rated for outdoor use
- Integrated with any SIP device



(E12 Video Door Intercom)



Cohesive Technologies Pvt. Ltd

Tel: +91 120 4830000 Email: info@cohtechnologies.com Web: www.cohesiveglobal.com

Cohesive E12 SIP Video Door Intercom



Physical & Power

Body Material: Plastic

Camera: 2M pixels, automatic lighting

• Button: 1 call button with backlight

Wiegand port: SupportRF card reader: 13.56MHz

Light sensor: 1Relays out: 1

Inputs: 2

Micro SD card slot: 1
Microphone: -36dB
Speaker: 8Ω / 1.5W

Ethernet port: RJ45, 10/100Mbps adaptive

BLE: Yes

Vandal alarm: Yes

802.3af Power-over-Ethernet

12V DC connector (if not using PoE)

Power: 12V / 1A

Water-proof & Dust-proof: IP65

Installation: Wall-mounted

Size: 146x70x23mm

Working Humidity: 10~90%

Working Temperature: -40°C ~ +60°C
 Storage Temperature: -40°C ~ +70°C

Audio

SIP v1 (RFC2543), SIP v2 (RFC3261)

Narrowband audio codec: G.711a, G.711µ, G.729

Broadband audio codec: G.722

DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info

Echo Cancellation

Voice Activation Detection

Comfort Noise Generator

Video

Sensor: 1/2.7", CMOS

Pixels: CIF, QCIF, VGA, 4CIF, 720p, 1080p

Video codec: H.264, H.265

Video resolution: up to 1920x1080p

Max. image transfer rate: 1080p – 25fps

Viewing angle: 123°(H) / 69°(V)

White LEDs for picture lighting during dark hours with internal light sensor

Door Entry Feature

Relays controlled individually by DTMF tones

Camera permanently operational

Auto-night mode with LED illumination

White balance: auto

Minimum illumination: 0.1LUX

Networking & Protocol

 Protocols support: IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Deployment & Maintenance

Auto-Provisioning

Web management portal

Configuration backup / restore

Entry log export

Access table export / import

Firmware upgrade

System logs (include door access logs)

Application Scenario

Apartment/flat intercom with door access control

Remote site entry over Internet



Cohesive Technologies Pvt. Ltd

Tel: +91 120 4830000 Email: info@cohtechnologies.com Web: www.cohesiveglobal.com