

		
	<b>GDS3705</b>	<b>GDS3710</b>
<b>Lens Type</b>	N/A	1/2", F2.5, FOV: 180°(W) x 150°(H)
<b>Day/Night Features</b>	N/A	White LEDs with smart brightness control
<b>Video Resolution</b>	N/A	1920x1080
<b>Video Compression</b>	N/A	H.264, Motion JPEG
<b>SIP/VoIP Support</b>	Yes	Yes
<b>Network Interface</b>	10M/100M Auto-Sensing Port	10M/100M Auto-Sensing Port
<b>Expansion Interface</b>	RS485, Wiegand 26 Input and Output	RS485, Wiegand 26 Input and Output
<b>Power Supply</b>	PoE (IEEE 802.3af Class 3), or 12VDC/1A Connection	PoE (IEEE 802.3af Class 3), or 12VDC/1A Connection
<b>Audio Input</b>	Built-in Dual Microphone, Up To 1.5m	Built-in Microphone, Up To 1.5m
<b>Audio Output</b>	Built-in HD Loudspeaker, Up To 3m, AEC	Built-in HD Loudspeaker, Up To 3m, AEC
<b>Alarm In</b>	2 channels, Vin < 15V	2 channels, Vin < 15V
<b>Alarm Out</b>	2 channels, 125VAC/0.5A, 30VDC/2A	2 channels, 125VAC/0.5A, 30VDC/2A
<b>Keypad</b>	12-key Metal Keys, Metal Doorbell Button	12-key Touchpad, Capacitive Doorbell Button
<b>RFID Support</b>	125KHz: EM4100, Up To 2000 Cards Supported	125KHz: EM4100, Up To 2000 Cards Supported
<b>Voice Codecs</b>	G.711μ/a-law, G.722	G.711μ/a-law, G.722
<b>Security</b>	MD5 and MD5-sess, 256-bit, AES, TLS, SRTP, HTTPS, 802.1Q	MD5 and MD5-sess, 256-bit, AES, TLS, SRTP, HTTPS, 802.1Q
<b>Provisioning</b>	TFTP/HTTP/HTTPS, XML, TR-069 (Pending)	TFTP/HTTP/HTTPS, XML, TR-069 (Pending)
<b>ONVIF Compliant</b>	N/A	Yes – Profile S
<b>Enclosure Protection</b>	IP66 Weatherproof, IK09 Vandal Resistant	IP66 Weatherproof, IK09 Vandal Resistant