



Cordless Wi-Fi IP Phone

WP810

The WP810 is a portable Wi-Fi IP phone designed to suit a variety of enterprises and vertical market applications, including retail, logistics, medical and security. This basic cordless Wi-Fi phone comes equipped with integrated dual-band 802.11a/b/g/n/ac Wi-Fi, an advanced antenna design and roaming support. By adding 6-hour talk time and HD voice with dual-MICs, the WP810 offers an affordable option and comes equipped with a combination of features, mobility and durability to suit all portable telephony needs.



Dual-band Wi-Fi with efficient antenna design and advanced roaming support




2 SIP accounts, 2 lines



HD voice & dual MIC design with AEC and Noise Shield Technology



Rechargeable 1500mAh battery, 6 hour talk time, 120-hour standby



Configurable button for push-to-talk



Micro USB port and 3.5mm headset jack

| | |
|--|---|
| Protocol/Standards | SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, SSH, TFTP, NTP, STUN, SIMPLE, LLDP-MED, LDAP*, TR-069, 802.1x, TLS, SRTP, IPv6 |
| Voice Codecs and Capabilities | Support for G.711 μ /a, G.729A/B, G.722 (wide-band), iLBC, Opus, in-band and out-of-band DTMF (In audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJB, AGC, ANS |
| Graphic | 1.8 inch (128x160) TFT color LCD |
| Peripherals | 2 soft keys, dial, hangup, speakerphone, phonebook, backlit keypad, proximity sensor, vibration motor, volume button and navigation keys |
| Push-to-Talk | Customizable button for push-to-talk |
| Auxiliary Ports | 3.5 mm headset jack, Micro USB port for charging, dual-MIC, dual-color MWI LED |
| Telephony | Hold, transfer, forward, 3-way audio conference, downloadable phonebook (XML, LDAP, up to 500 items), call waiting, call log (up to 100 records), off-hook auto dial, auto answer, flexible dial plan, hot desking, personalized music ringtones, server redundancy and fail-over, push to talk |
| Security | User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES based secure configuration file, SRTP, TLS, 802.1x media access control |
| HD Audio | Yes, both on handset and speakerphone with support for wideband audio, HAC supported |
| QoS | 802.11e and Layer 3 (ToS, DiffServ, MPLS) QoS |
| Multi-language | English, Arabic*, Chinese, Czech, Dutch, German, French, Hebrew*, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Turkish and more |
| Upgrade/Provisioning | Firmware upgrade via TFTP/HTTP/HTTPS, mass provisioning using TR-069 or encrypted XML configuration file, manual upload |
| Power & Green Energy Efficiency | Universal power adapter included Input: 100-240VAC; Output: +5VDC, 1A (5W) 1500mA Li-ion battery, 120h standby time and 6h talk time |
| Physical | Headset dimensions: 158.5 x 50 x 22.5mm Charger cradle dimensions: 81.15 x 75.89 x 36.36mm Handset weight: 120g Handset package weight (not including QIG): 340g |
| Temperature and Humidity | Operating Temperature: 0°C to 45°C; Operating Humidity: 10-90% (non-condensing) Storage Temperature: -20°C to 60°C; Storage Humidity: 10%-90% (non-condensing) |
| Package Contents | Handset unit, universal power supply, charger cradle, belt clip, 1 Li-ion battery, Quick Start Guide |
| Compliance | FCC, CE, RCM, IC |