

Tonmind 30W IP Horn Speaker SIP-S21M

1. Two-Way Intercom Communication.
2. 48K OPUS, AEC, AGC, ANR
3. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
4. Compatible with IP Camera VMS via ONVIF.
5. HTTP Control, Alarm in, Schedule
6. 30W Amplifier, PoE Power Supply
7. Built-in MIC, Audio in, TF Card (Optional)



Specification:

Audio	
Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
Built-in Microphone	Yes
Speaker	
Max SPL	120dB
Frequency Response	350Hz~8KHz
Frequency Range	500-2KHZ +-10dB 400-12KHZ +-20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB
Network	
Security:	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
	Support for SIP protocol for intergration with VoIP systems, intergrated with SIP/PBX.
VoIP	2 SIP Accounts, SIP Direct IP Call, RTP Multicast
	Codec: OPUS, MP3, G.722, PCMU, PCMA
Amplifier	
Amplifier Description	Built-in 30W Amplifier
General	
Operating Temperature	-30℃ — +60℃
Operating humidity	5%-85%
Material	ABS (IP67 water-proof)
Rate Power	30W
Power Supply	PoE or DC 12V/24V
Connector	Alarm in, Audio in, DC Power, PoE, TF Card (Optional)
Installation	Wall Mounted
Dimensions	285*205*290mm
Net Weight	2 KG
Languages	English
Warranty	2 years
Package Includes	IP Horn Speaker User Manual