

Tonmind 15W IP Horn Speaker SIP-S21H

1. Two-Way Intercom Communication.
2. 48K OPUS, AEC, AGC, ANR
3. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
4. Compatible with IP Camera VMS via ONVIF.
5. HTTP Control, Alarm in, Schedule
6. 15W Amplifier, PoE Power Supply
7. Built-in MIC



Specification:

Audio

Codec: OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

Built-in Microphone: Yes

Speaker

Max SPL: 113dB

Frequency Response: 300Hz~8KHz

Frequency Range: 500-2KHZ +-10dB
400-12KHZ +-20dB

Harmonic Distortion: 0.1@1kHz

Signal to Noise Ratio: 91dB

Network

Security: Password protection, IP address filtering, Digest authentication, User access log, firewall

Network Protocol: SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP

Network Interface: 10/100 Base-TX, RJ45

Support for SIP protocol for intergration with VoIP systems, intergrated with SIP/PBX.

VoIP: 2 SIP Accounts, SIP Direct IP Call, RTP Multicast

Codec: OPUS, MP3, G.722, PCMU, PCMA

Amplifier

Amplifier Description: Built-in 15W Amplifier

General

Operating Temperature: '-30 °C — +60 °C

Operating humidity: 5%-85%

Material: ABS (IP67 water-proof)

Rate Power: 15W

Power Supply: PoE or DC 12V/24V

Connector: Alarm in, Audio in, DC Power, PoE, TF Card (Optional)

Installation: Wall Mounted

Dimensions: 225*165*240mm

Net Weight: 1.3 KG

Languages: English

Warranty: 2 years

Package Includes: IP Horn Speaker
User Manual