

Tonmind 15W IP Ceiling Speaker with MIC SIP-S01M

1. Two-way intercom communication.
2. PoE eliminates need for local power supply.
3. 48K OPUS Audio Codec enables excellent sound quality.
4. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
5. Compatible with IP Camera VMS via ONVIF.
6. Support Pre-recorded messages.
7. Support HPPT API for alarm in transmit.



Specification:

Audio

Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
-------	---

Speaker

Max SPL	96dB
Frequency Response	100Hz ~ 18KHz
Frequency Range	500-2KHZ +-10dB 400-12KHZ +-20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB

Network

Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
	Support for SIP protocol for intergration with VoIP systems, intergrated with SIP/PBX.
VoIP	2 SIP Accounts, SIP Direct IP Call, RTP Multicast
	Codec: OPUS, MP3, G.722, PCMU, PCMA

Amplifier

Amplifier Description	Built-in 15W Amplifier
-----------------------	------------------------

MIC

Built-in MIC	Yes
--------------	-----

General

Material	Metal
Rate Power	15W
Power Supply	PoE or DC 12V/24V
Installation	In Ceiling
Dimensions	200 x 90 mm
Net Weight	1 KG
Languages	English
Warranty	2 years
Package Includes	Network Ceiling Speaker User Manual