

## Tonmind 50W IP Horn Speaker SIP-S25V

1. Built-in 50W amplifier for powerful and clear audio output.
2. Max SPL 128 dB for long-distance sound coverage.
3. Supports SIP protocol for VoIP paging integration.
4. ONVIF compatible for VMS and NVR connectivity.
5. PoE and DC power supply options for flexible installation.
6. Durable IP66 aluminum housing for outdoor environments.
7. Supports multiple audio decoding formats for versatile streaming.



### Specification:

Audio	
Decoding	OPUS 48KHz, MP3 44.1KHz, G.722-ADPCM 16KHz, G.711-PCMU 8KHz, G.711-PCMA 8KHz, G726 8KHz, GSM 8KHz, LPCM-16bit-Stereo/Mono 44.1kHz
Speaker	
Max SPL	128dB
Frequency Response	150Hz-8kHz
Network	
Security	Password protection, IP address filtering, Digest authentication, User access log, Firewall
Network Protocol	SIP, ONVIF, HTTP, HTTPS, IPv4, TLS, RTSP, RTP, RTCP, DHCP, DNS, NTP, TCP, UDP, IGMP, ICMP, ARP
Network Interface	10/100 Base-TX, RJ45
	Supports the SIP protocol for integration with VoIP systems and SIP/PBX platforms.
SIP Features	Supports secondary/backend SIP server, IPv4 (IPv6 in development).
	Supports codecs: OPUS, G722, G711U, G711A.
	SIP DTMF (RFC 2976, RFC 2833/RFC 4733)
Amplifier	
Amplifier Description	Built-in 50W Amplifier
General	
Operating Temperature	-30°C — +60°C
Operating Humidity	5%-85%
Material	Aluminum (IP66)
Rate Power	50W
Power Supply	DC24V
Interface	RJ45, DC Power Input
Installation	Bracket Mount
Dimensions	Dia 16inch
Net Weight	3.4kg
Languages	English
Warranty	2 years
Package Includes	IP Horn Speaker Quick Guide