

Tonmind 30W IP Pendant Speaker SIP-S61M

1. Transfer loud and excellent sound.
2. 48K OPUS, AEC, AGC, ANR
3. Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
4. Compatible with IP Camera VMS via ONVIF.
5. HTTP Control, Alarm in, Schedule
6. 30W Amplifier, PoE Power Supply
7. Support Pre-recorded messages event
8. Built-in MIC



Specification:

Audio

Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
Built-in Microphone	Yes

Speaker

Max SPL	91dB
Frequency Response	70Hz~20KHz
Frequency Range	500-2KHZ +-10dB 400-12KHZ +-20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB

Network

Security:	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
	Support for SIP protocol for intergration with VoIP systems, intergrated with SIP/PBX.
VoIP	2 SIP Accounts, SIP Direct IP Call, RTP Multicast
	Codec: OPUS, MP3, G.722, PCMU, PCMA

Amplifier

Amplifier Description	Built-in 30W Amplifier
-----------------------	------------------------

General

Operating Temperature	'-30°C — +60°C
Operating humility	5%-85%
Material	ABS
Rate Power	30W
Power Supply	PoE
Connector	PoE
Installation	Pendant
Dimensions	D185*250mm
Net Weight	2.1KG
Languages	English
Warranty	2 years
Package Includes	IP Pendant Speaker User Manual