

Tonmind 15W IP Horn Speaker SIP-S26H

1. Built-in Ethernet port and interfaces for easy connection and clean design.
2. Durable ASA material suitable for harsh outdoor environments.
3. Built-in microphone supports two-way intercom communication.
4. Supports real-time voice recording.
5. Large built-in storage can store recordings and audio files.
6. Compatible with standard SIP and ONVIF protocols.
7. PoE eliminates the need for local power supply.
8. Supports RTP Multicast, pre-recorded messages, schedule, and HTTP API.



Specification:

Audio	
Decoding	OPUS 48KHz, MP3 44.1KHz, G.722-ADPCM 16KHz, G.711-PCMU 8KHz, G.711-PCMA 8KHz, G726 8KHz, GSM 8KHz, LPCM-16bit-Stereo/Mono 44.1kHz
MIC	
Built-in Microphone	YES
Speaker	
Max SPL	113dB
Frequency Response	300Hz~8KHz
Frequency Range	500-2KHZ +- 10dB 400-12KHZ +- 20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB
Network	
Security	Password protection, IP address filtering, Digest authentication, User access log, Firewall
Network Protocol	SIP, ONVIF, HTTP, HTTPS, IPv4, TLS, RTSP, RTP, SRTP, RTCP, DHCP, DNS, NTP, TCP, UDP, IGMP, ICMP, ARP, SNMP v1/v2c/v3, Bonjour
Network Interface	10/100 Base-TX, RJ45
SIP Features	Supports the SIP protocol for integration with VoIP systems and SIP/PBX platforms.
	Supports secondary/backend SIP server, IPv4 (IPv6 in development).
	Supports codecs: OPUS, G722, G711U, G711A. SIP DTMF (RFC 2976, RFC 2833/RFC 4733)
Amplifier	
Amplifier Description	Built-in 15W Amplifier
General	
Operating Temperature	-30°C — +60°C
Operating humidity	5%-85%
Material	ASA (durable and water-proof)
Rate Power	15W
Power Supply	PoE
Interface	RJ45, IO Input, IO Output, DC 12V Output, Reset Button, MIC Control Switch
Installation	Wall Mounted
Dimensions	225 × 165 × 240mm
Net Weight	1.4 KG
Languages	English, Italian, Russian, Korean, Chinese Simplified & Traditional
Warranty	2 years
Package Includes	IP Horn Speaker Quick Guide