

Tonmind SIP Paging Adapter SIP-T20

1. Two-way intercom communication
2. Support 48K OPUS Audio Codec
3. SIP & Onvif protocol compatibility
4. Pre recorded message(WAV/MP3)
5. Alarm: GPIO, HTTP URL, and relay out
6. MIC, headset and speaker interface
7. Reset and volume control



Specification:

Audio

Decoding	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
----------	---

Network

Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
	Support SIP protocol for intergration with VoIP systimes, intergrated with SIP/PBX.
VoIP	Support SIP features: secondary/backend SIP server, IPv4 (IPv6 futhur).
	Support codecs: OPUS, G711U, G711A, GSM, MP3, WAV.

Amplifier

Amplifier description	Built-in 15W Amplifier
-----------------------	------------------------

General

Material	Metal
Power Supply	PoE or DC 12V/24V
Interface	1* MIC input, 1* Headset output, 1* Speaker output, 2* GPIO Alarm input, 1* GPIO Alarm output, 2* Relay Alarm output
Dimensions	112mm *105mm * 29mm
Weight	250g
Languages	English
Warranty	2 years
Package includes	SIP Paging Adapter User Manual